

TEXT DISPLAY

OP320-A-S

- Display Type: Yellow-green LCD
- Life More than 20,000 hours, an ambient temperature of 25, 24-hour operation
- Resolution: 192*64 pixels
- Display : 3.7 Monochrome STN LCD with back light
- Brightness: Potentiometer adjustable
- Text Settings: Simplified English
- Character size: Bitmap fonts, vector fonts
- Button: 20
- Menu: 64KB FlashROM
- Data: 1KB SRAM
- Download port: RS232
- Communication port: RS232 /RS485
- Voltage range: DC22V-DC26V
- Power consumption: < 4W
- Allowable Voltage: 10mS (actual loss of power is less than 1 second)
- Withstand voltage : AC1000V, 10mA less than 1 minute
- Operating temperature: 0-50 degrees
- Storage Temperature: -10-60 Degrees
- Ambient humidity: 20% RH to 85% RH (non-condensing)
- Anti-jamming capability: Interfere with air pressure: 1000Vp-p Pulse cycle:
1ms, Duration: 1 min
- Protection Structure : IP65F
- Cooling method: Natural air-cooled
- Size: 172x94x30 mm
- Supports most of the PLCs like Delta ,Mitsubishi, Omron, AB, Siemens S7-200 etc.,

Download / Com port

OP320-A-S

Pin no.	Function
Pin1	TD+
Pin2	RXD
Pin3	TXD
Pin4	
Pin5	GND
Pin6	TD-
Pin7	RTS
Pin8	B
Pin9	A

Unit: mm







