

TEXT DISPLAY

OP320-A

- Type: Yellow-green LCD
- Life More than 20,000 hours, an ambient temperature of 25, 24-hour operation
- Display area: 192*64
- Brightness: Potentiometer adjustable
- Text Settings: Simplified English
- Character size: Bitmap fonts, vector fonts
- Button: 20
- Menu: 64KB FlashROM
- Data: 1KB SRAM
- Download port: RS232
- Communication port: RS232 /RS485
- Voltage range: DC12V-DC24V
- Current consumption: <140mA
- Allowable Voltage: 10mS (actual loss of power is less than 1 second)
- Anti-voltage surge: AC1000V, 20mA less than 1 minute
- Insulation resistance: 10M, DC500V
- Operating temperature: 0-50 degrees
- Storage Temperature: -20-60 Degrees
- Operating humidity: 10% RH to 90% RH (non-condensing)
- Anti-jamming capability: Interfere with air pressure: 1500Vp-p Pulse cycle: 1uS In
Duration: 1 min
- Air: Non-corrosive gases
- Cooling method: Natural air-cooled
- Size: 17.1x9.3x3cm/6.73x3.66x1.18inch
- Supports most of the PLCs like Delta, Mitsubishi, Omron, AB, Siemens s7-200 etc.,







