

## XINJE TOUCH SCREEN

### TG765S-XT

- Dimension(inch) : 7
- Resolution : 800\*480
- LCD: TFT LCD, LED backlight
- Color: 16.77 million true colors
- Bright: 200
- Touch panel: 4-wire resistor touch screen
- LCD life: Above 50000 hours, ambient temperature 25°C, 24 hours running
- Memory: 128MB
- Download port: RS232
- PLC port: RS232
- USB port1 : USB-B (USB 2.0 standard), USB download port
- Input voltage : DC24V (voltage range: DC22V~26V)
- Consumption current : 200 mA
- Allowable power-off : 1Under 10ms (actual power-off is less than 1s)
- Voltage shock endurance : AC1000V, 10mA less than 1 minute (between signal and ground)
- Insulation resistance : Above 10MΩ, DC500V
- Operating temperature : 0~50°C
- Storage temperature : -20°C~60°C
- Operating humidity : 10%RH~90%RH (no condensation)
- Anti-interference ability : Interference voltage: 1500 Vp-p, pulse period: 1μs, duration time: 1 minute
- Ambient : No corrosive gas
- Cooling mode : Natural cooling
- Protection level : IP65 for front cover
- Model explanation: XT: USB-B port, real-time clock

- Dimension (mm) : 205.4\*146.5\*38.5
- Mounting dimension (mm) : 192.0\*138.5
- Supports most of the PLCs like Delta ,Mitsubishi, Omron, AB, Siemens S7-200, Xinje etc.,



